

PIR Jars and Caps







Features & Benefits

- Made from plastic destined for landfills Environmentally friendly by minimizing the use of new raw materials
- Recycled resin base is cleaned to the highest standards Perfectly safe for cosmetics and skincare products
- Same material profile as standard polypropylene Additional compatability or stability testing may not be needed
- Made in USA Timely availability with world-class environmental and quality standards

Jar Specifications

Capacity	Style	Size	Outside Diameter	Overall Height	Fill to Overflow	Deco Area (H x Cir)
0.5 fl oz/15 ml	SR	48mm	2.03"	1.27"	0.76 fl oz/22.5 ml	0.42" X 5.92"
	SB	48mm	2.03"	1.27"	0.76 fl oz/22.5 ml	0.62" X 6.08"
1 fl oz/29.6 ml	SB	53mm	2.16"	1.64"	1.5 fl oz/44 ml	0.92" X 6.52"
2 fl oz/59 ml	SR	58mm	2.35"	1.96"	2.59 fl oz/77 ml	1.00" X 7.12"
	SB	58mm	2.35"	1.96"	2.59 fl oz/77 ml	1.22" X 7.12"
2 fl oz/59 ml	SR	70mm	2.91"	1.48"	2.58 fl oz/76.3 ml	0.54" X 8.84"
	SB	70mm	2.90"	1.48"	2.54 fl oz/76 ml	0.75" X 8.84"
4 fl oz/118 ml	SR	70mm	2.89"	2.42"	5.1 fl oz/151.4 ml	1.34" X 8.80"
	SB	70mm	2.90"	2.44"	5.1 fl oz/151.4 ml	1.62" X 8.80"
4 fl oz/118 ml	SR	89mm	3.65"	1.77"	6.1 fl oz/180 ml	0.60" X 11.19"
8 fl oz/237 ml	SR	89mm	3.66"	2.64"	9.35 fl oz/276.5 ml	1.44" X 11.20"
	SB	89mm	3.68"	2.65"	9.35 fl oz/276.5 ml	1.62" X 11.20"

Cap Specifications Provided on Reverse Side

Description

PIR (Post Industrial Resin) is a blend of recycled polypropylene resins that offer affordable and environmentally responsible packaging—good for the earth, good for your brand and great for your business! Twelve jars and four caps available in a rustic matte black finish

Decoration Options

- Silk-screen Jar
- Offset printing Cap

To place an order or get more information, please contact your CSI Sales and Customer Service Representative:

550 East Third Street Oxnard, CA 93030 Phone (805) 487-6698 Fax (805) 487-1967 info@csillc.com

www.CSILLC.com









PIR Jars and Caps

Cap Specifications

Style	Size	Outside Diameter	Overall Height	Deco Area (Diameter)
DOME	58mm	2.34"	0.67"	1.35"
DOME	70mm	2.88"	0.67"	1.70"
SS	89mm	3.63"	0.61"	3.50"
SS	89mm XT	3 63"	1.00"	3 50"